

Overview

# TX Table Hub.

Signal input box that is installed under a table, in a lectern or wherever you want to connect laptop/devices.

- Two inputs provided:
- USB-C (4K video, audio, USB, network, control)
  - HDMI (4K)

Provides laptop charging power via USB-C

- Connect optional Ashton Bentley **Tablebox**:
- Retractors for improved cable management with retractors
  - Touch Panel for enhanced input signal selection (including 2 x Aux HDMI inputs on DX)

USB-C to USB-A converter included (use HDMI + USB-A for BYOM)

Connection	Type	Function
ABUS	RJ45	Cat6A interconnection to DX
LOCAL NETWORK	RJ45	Network connection to USB-C (local or from DX)
SERVICE	2.5mm 4 pole jack	Service Port
ABNET	RJ45	Control / Power bus. For optional accessories such as Tablebox
HDMI	HDMI (locking)	HDMI 4K Laptop (or other device) connection
USB-C	USB-C (locking)	USB-C Laptop (or other device) connection



Connection Plate 1



Connection Plate 2



# TX Table Hub.

**Power Rating:**

56 V POE 1.8A

**Power Consumption:**

100W (Max)

**Supplied with:**

Interconnect to DX Cat6A Cable (10m)

USB-C Laptop Input Cable with locking connector (2.5m)

HDMI Laptop Input Cable with locking connector (2.8m)

**LED Status Information:**


ST: Status of unit

LINK: Confirm connection to DX Table Hub

FW: Show status of Link Controller

PWR: Confirm unit powered

*See manual for more detail*



ISOMETRIC VIEW

